



Pallet Shippers

PRODUCT RANGE



SPECIFICATIONS:

Models available to accommodate 1200mm x 800mm Euro Skids, 1200 x 1000mm Euro Pallets and 1190 x 1170 Australian and USA Pallet sizes.

The pallets are designed to fit in wide or narrow body aircraft doors and perfect for reducing export costs.

The pallet shippers are delivered as a complete kits, fitted with phase change gel sleeves, ready for conditioning and use.

KEY FEATURES:

EPS, XPS, PU, VIP insulation
425L - 3,500L Payload
72-144 Hour Validation
Australian Summer/Winter (ASW)
International (ISTA/INT)
Front or top loaded options available



CONTACT US FOR MORE INFORMATION:

Australia:	Ph: +61 (03) 93303603	Email: info@globalcoldchain.com
India:	Ph: +91-93-13 35 02 58	Email: india@globalcoldchain.com
Germany:	Ph: +49 (0)7761 556 8650	Email: europe@globalcoldchain.com
Malaysia:	Ph: +60 (0)16 5230460	Email: info@globalcoldchain.com



+2°C to +8°C

MODEL	LOAD	HOURS	PROFILE	INTERNAL (MM)	EXTERNAL (MM)	PAYLOAD
TPC-320-122+2+8-102-ASW	T	102	ASW	782x710x970	1060x710x970	122
TPC-425-318+2+8-72-INT	T	72	INT	1010x610x567	1180x780x980	318
TPC-645FT-553+2+8-79-INT	F/T	79	INT	1065x865x600	1250x1040x1020	553
TPC-977-832+2+8-89-INT	F	89	INT	1030x640x1104	1225x925x1555	732
TPC-1169-692+2+8-72-INT	F	72	INT	980x760x930	1250x1050x1550	692
TPC-1261-1019+2+8-89-INT	F	89	INT	860x1040x1100	1040x1320x1580	1019

+2°C to +25°C

MODEL	LOAD	HOURS	PROFILE	INTERNAL (MM)	EXTERNAL (MM)	PAYLOAD
TPC-425-243+2+25-47-ASW	T	47	ASW	900x500x560	1175x715x910	243
TPC-645FT-351+2+25-144-ISTA	F/T	144	ISTA	940x740x505	1235x1035x1000	351
TPC-645FT-413+2+25-72-ASW	F/T	72	ASW	955x755x590	1235x1035x1000	413
TPC-977-555+2+25-144-ISTA	F	144	ISTA	904x634x970	1210x910x1570	555
TPC-977-656+2+25-72-ASW	F	72	ASW	930x635x1095	1210x910x1570	656
TPC-1169-798+2+25-72-ASW	F	72	ASW	980x760x930	1250x1050x1545	798
TPC-1261-833+2+25-72-ASW	F	72	ASW	775x1040x1040	1040x1320x1580	833

+15°C to +25°C

MODEL	LOAD	HOURS	PROFILE	INTERNAL (MM)	EXTERNAL (MM)	PAYLOAD
TPC-425-349+15+25-96-INT	T	96	INT	110x610x567	1180x780x980	349
TPC-645FT-553+15+25-96-INT	F/T	96	INT	1065x865x600	1250x1040x1020	553
TPC-977-728+15+25-96-INT	F	96	INT	1030x640x1104	1225x925x1555	728
TPC-1169-692+15+25-96-INT	F	96	INT	980x760x930	1250x1050x1550	692
TPC-1261-983+15+25-96-INT	F	96	INT	860x1040x1100	1040x1320x1580	983
TPC-1737-1270+15+25-100-INT	F	100	INT	900x1255x1125	1528x1158x1572	1270
TPC-425-252+15+25-47-ASW	T	47	ASW	900x500x560	1180x780x980	252
TPC-645FT-336+15+25-66-ASW	F/T	66	ASW	565x765x630	1250x1040x1020	465
TPC-997-646+15+25-65-ASW	F	65	ASW	930x635x1095	1225x925x1555	646
TPC-1169-692+15+25-65-ASW	F	65	ASW	980x760x930	1250x1050x1550	692
TPC-1261-838+15+25-89-ASW	F	89	ASW	775x1040x1040	1040x1320x1580	838

-16°C

MODEL	LOAD	HOURS	PROFILE	INTERNAL (MM)	EXTERNAL (MM)	PAYLOAD
TPC-425-110-16-72+25	T	72	-	725x390x390	1180x780x980	110
TPC-1169-564-16-120+25	F	120	-	860x665x987	1250x1050x1550	564
TPC-1261-688-16-120-INT	F	120	INT	690x950x1050	1040x1320x1580	688



-22°C

MODEL	LOAD	HOURS	PROFILE	INTERNAL (MM)	EXTERNAL (MM)	PAYLOAD
TPC-425-216-22-16-75-ISTA	T	75	ISTA	470x470x530	1180x780x980	216
TPC-645-362-22-16-90-ISTA	F/T	90	ISTA	925x725x540	1235x1045x1025	362
TPC-1169-564-22-120+25	F	120	-	690x950x1050	1250x1050x1550	564
TPC-1261-711-22-72-INT	F	72	INT	655x1025x1060	1040x1320x1580	711

-33°C

MODEL	LOAD	HOURS	PROFILE	INTERNAL (MM)	EXTERNAL (MM)	PAYLOAD
TPC-425-110-33-95+25	T	95	-	725x390x390	1180x780x980	110

-80°C Dry Ice

MODEL	LOAD	HOURS	PROFILE	INTERNAL (MM)	EXTERNAL (MM)	PAYLOAD
TPC-425-295-70-141-INT	T	141	INT	1010x610x480	1180x780x980	295
TPC-645-258-70-141-SUM	F/T	141	AS	702x567x649	1235x1045x1025	258
TPC-645-451-70-150-INT	F/T	150	INT	1065x865x490	1235x1045x1025	451
TPC-425-80-150-INT	T	72	INT	1010x610x690	1180x780x980	425
TPC-425-80-150-INT	T	72	INT	1065x865x700	1235x1045x1000	645
TPC-900-557-70-144-ISTA	F	144	ISTA	930x930x645	1200x1200x1085	557
TPC-900-740-80-144-ISTA-SUM	F	144	ISTA	900x900x785	1200x1200x1100	740